



MODEL A10160

45MHz 34Vp-p Single Channel Signal Amplifier

- 45MHz bandwidth
- High amplitude to 34Vp-p into 50
- High output current drive to 1A
- Fast transition time of <10ns
- Small footprint, all metal case
- Custom gain configuration
- Low distortion

Model A10160 is an ultra-small footprint, wideband, DC coupled amplifier designed for high frequency, high current, signal amplification. With a high bandwidth of 45MHz, 34Vp-p into 50 ohms and up to 10W output power, the A10160 is the ideal complimentary amplifier to any signal source that needs a supporting power boost for demanding applications.

Enhancing Performance

The A10160 was designed as a “Snap-On” accessory for the Tabor WaveXciter series and models WS8351/2, both having a maximum amplitude of 4Vp-p, which can be limiting for some applications, requiring higher voltage and current to drive their UUT. Combined with the A10160 the WX and WS models will now offer even higher abilities to solve demanding application requiring up to 45MHz signals at 34Vp-p into 50 ohms loads, without compromising their signal integrity.

High Current High Power

With a peak output current of 1A and 750mA continuous the A10160 enables a continuous power output of 7.5W, and a peak output power of up to 10W, making it ideal for various pulse applications.

Cost Effective Versatile Solution

While the A10160 was designed with the Tabor units in mind, it can be used as a standalone amplifier for any signal source. The A10160 offers a compatible, compact and cost effective solution for extending any signal source’s power performance.

Optional Configurations

The A10160’s standard configuration enables a maximum output voltage of 34Vp-p into 50 ohms with a gain of x10. Other custom gain, such as x15 or 20 can be ordered at the time of the purchase, enabling clients’ even wider variety of choices to solve their application.

Target Applications

While target applications include piezo-electronics, transducer characterization, MEMS, general electronics and scientific applications, the new A10160 is an ideal solution for virtually any wide bandwidth application that requires high voltage and high current amplification.



MODEL A10160

45MHz 34Vp-p Single Channel Signal Amplifier

Specification

INPUT CHARACTERISTICS

Channels: 1
Type: Single Ended
Connector: Front panel SMA
Impedance: 50Ω
Coupling: DC
Damage Level: 6Vp-p (-3V to +3V peaks)
Frequency Range: DC to 45MHz

OUTPUT CHARACTERISTICS

No. of Channels: 1
Type: Single Ended
Coupling: DC coupled
Connector: Rear panel BNC
Gain: x10, fixed (x15 gain optional)
Polarity: Normal
Amplitude:
 Peak 34Vp-p into 50Ω
 Continuous 30Vp-p into 50Ω

Max. Output Current:

Peak 1A
 Continuous 750mA

Impedance: 2.5Ω ±5%

Protection: Short Circuit to Case Ground & thermal protection

SQUARE WAVE CHARACTERISTICS

Transition Time: <10ns (typ.)

Aberration:

10Vpp <5%
 34Vpp <10%

GENERAL

Voltage: ±20VDC
Power Consumption: 20W
Signal Ground: Grounded
Dimensions: 45 x 30 x 85 mm (W x H x D)
Weight:
 Without Package 115 g (Standalone)
 Shipping Weight
 1 x A10160 Kit 1.25 Kg
 2 x A10160 Kit 1.45 Kg
Temperature:
 Operating 0°C to 40°C
 Storage -40°C to 70°C

Humidity: 80% RH, non-condensing

Safety: CE Marked, IEC61010-1

Calibration: 1 years

Warranty*: 3 year standard

* 1 year standard in India

SINE WAVE CHARACTERISTICS

Bandwidth (-3dB):

<10Vpp 45MHz (typ.)
 <34Vpp 30MHz (typ.)

Harmonics & Non-Harmonic Distortion (typ.)

	10Vpp	25Vpp
1MHz	<-58dBc	<-54dBc
10MHz	<-45dBc	<-45dBc
30MHz	<-42dBc	<-30dBc

ORDERING INFORMATION

MODEL	DESCRIPTION
A10160-10 ⁽¹⁾	45MHz 34Vp-p, Single Channel Signal Amplifier
Gain:	10 = x10 gain, fixed 15 = x15 gain, fixed 20 = x20 gain, fixed

⁽¹⁾ Standard Configuration

⁽²⁾ Specification is given for the standard configuration only



绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室
 深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋607
 南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号
 广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房
 电话：020-2204 2442
 传真：020-8067 2851
 邮箱：Sales@greentest.com.cn
 官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号